Garant

GARANT Master Steel FEED solid carbide drill, plain shank DIN 6535 HA, TiAIN, Ø DC h7 (mm or inch): 6,9 mm or inch



Order data

Order number	122435 6,9
GTIN	4045197786746
Item class	11E

Description

Version:

3-flute drill, specially developed for **use at very high feed rates**. Extremely suitable for **machines with high power** output and stable machining conditions.

- Special point geometry with stable cutting edges and large clearance at the centre permits very high feed rates.
- The patented point geometry is optimised for chip flow and generates low cutting forces with good chip breakage.
- With 145° point angle for low burr formation when drilling through holes.
- The sector-leading technology of the chisel point guarantees optimum self-centring behaviour and permits spot drilling on irregular surfaces. 3 guide chamfers guarantee a stable exit from the hole and an exact roundness of the hole.

Recommendation:

Maximum drilling depth:

flute length (see table) less $1.5 \times nominal \emptyset$.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

HB and HE shanks are available at the same price as HA.
For **HB shanks:** use order **No. 122436**.
For **HE shanks:** use order **No. 122435** + **129100HE**.

Standard: DIN 6537 K

Tolerance nominal Ø: h7

Number of cutting edges Z: 3

Tolerance nominal Ø: h7

recommended maximum drilling depth L₂: 23.7 mm

Overall length L: 79 mm

Shank Ø D_s: 8 mm

Feed f in steel < 1100 N/mm²: 0.37 mm/rev.

Technical description

Tolerance nominal Ø	h7
Feed f in steel < 1100 N/mm ²	0.37 mm/rev.
Shank Ø Ds	8 mm
Number of cutting edges Z	3
Flute length L _c	34 mm
Standard	DIN 6537 K
Nominal Ø D _c	6.9 mm
Overall length L	79 mm
recommended maximum drilling depth L_2	23.7 mm
Series	GARANT Master Steel
Coating	TiAIN
Tool material	solid carbide
Drill depth up to	4×D
Point angle	145 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	green
Type of product	Jobber drill

Services

129100 HE