

# GARANT Master Steel FEED solid carbide drill, Weldon shank DIN 6535 HB, TiAlN, Ø DC h7 (mm or inch): 11,4 mm or inch



#### Order data

Order number	122436 11,4
GTIN	4045197793195
Item class	11E

### Description

#### **Version:**

**3-flute drill**, specially developed for **use at very high feed rates**. Outstandingly suitable for machines with **high installed power** and stable machining conditions.

- Special cutter geometry with stable cutting edges and large clearance at the centre enables very high feed rates.
- The patented tip is optimised for chip flow and generates low cutting pressure with good chip breakage.
- · With a 145° point angle for low burrs on emerging from through holes.

The sector-leading technology of the chisel point guarantees optimum self-centring behaviour and permits spot drilling on irregular surfaces. 3 guide chamfers guarantee a stable exit from the hole and an exact roundness of the hole.

#### **Recommendation:**

#### **Maximum drilling depth:**

clamping slot length (see table) less  $1.5 \times nominal \emptyset$ .

#### **Note:**

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

Standard: DIN 6537 K
Tolerance nominal Ø: h7
Number of cutting edges Z: 3
Tolerance nominal Ø: h7

recommended maximum drilling depth L₂: 37.9 mm

Overall length L: 102 mm Shank Ø D<sub>s</sub>: 12 mm

Feed f in steel < 1100 N/mm<sup>2</sup>: 0.5 mm/rev.

## **Technical description**

Feed f in steel < 1100 N/mm <sup>2</sup>	0.5 mm/rev.
Nominal Ø D <sub>c</sub>	11.4 mm
Standard	DIN 6537 K
Overall length L	102 mm
Shank Ø D <sub>s</sub>	12 mm
Tolerance nominal Ø	h7
Number of cutting edges Z	3
Flute length L <sub>c</sub>	55 mm
recommended maximum drilling depth L <sub>2</sub>	37.9 mm
Series	GARANT Master Steel
Coating	TiAIN
Tool material	solid carbide
Drill depth up to	4×D
Point angle	145 degrees
Shank	DIN 6535 HB to h6
Through-coolant	Yes, with 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	green
Type of product	Jobber drill