

HOLEX Pro Steel solid carbide drill, plain shank DIN 6535 HA, TiAIN, Ø DC h7 (mm or inch): 11,3 mm or inch



Order data

Order number	122501 11,3
GTIN	4045197825025
Item class	12F

Description

Version:

HOLEX Pro Steel:

Straight major cutting edges and a **special flute profile** ensure good chip evacuation. The robust cutter geometry ensures high-performance drilling with good process reliability. A wide range of applications in steel materials thanks to a combination of tough ultra-fine grain carbide and an extremely wear-resistant coating.

Up to \emptyset 1.9 with 4 facets, from \emptyset 2 with relieved cone.

Cutting chisel edge with high centring accuracy due to strong core and special point geometry. Straight major cutting edges with slightly honed edges and special flute profile produce short chips.

Recommendation:

Maximum drilling depth:

flute length (see table) less 1.5 \times nominal \varnothing .

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Version HB and HE supplied at the same price as HA.

Form **HB:** state **No. 122502**. Form **HE:** state **No. 122503**. Machining strategy: HPC Standard: DIN 6537 K Tolerance nominal Ø: h7 Number of cutting edges Z: 2

recommended maximum drilling depth L₂: 38.1 mm

Overall length L: 102 mm Shank Ø D_s: 12 mm

Tolerance nominal Ø: h7

Feed f in steel < 900 N/mm²: 0.22 mm/rev.

Technical description

Nominal Ø D _C	11.3 mm
Nothinal & D _C	11.511111
recommended maximum drilling depth L ₂	38.1 mm
Feed f in steel < 900 N/mm ²	0.22 mm/rev.
Flute length L _c	55 mm
Shank Ø D _s	12 mm
Tolerance nominal Ø	h7
Number of cutting edges Z	2
Standard	DIN 6537 K
Overall length L	102 mm
Series	HOLEX Pro Steel
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	4×D
Point angle	140 degrees
Shank	DIN 6535 HA to h6
Through-coolant	no
Machining strategy	HPC
Colour ring	green
Type of product	Jobber drill