



## HOLEX Pro Steel solid carbide drill, Weldon shank DIN 6535 HB, TiAlN, Ø DC h7 (mm or inch): 4,7 mm or inch



### Order data

Order number	122502 4,7
GTIN	4045197830586
Item class	12F

### Description

#### Version:

**Straight major cutting edges** and a **special flute profile** ensure good chip evacuation. The robust cutter geometry ensures high-performance drilling with good process reliability. A wide range of applications in steel materials thanks to a combination of tough ultra-fine grain carbide and extremely wear-resistant coating.

#### Recommendation:

##### Maximum drilling depth:

clamping slot length (see table) less  $1.5 \times \text{nominal } \varnothing$ .

##### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

Machining strategy: HPC

Standard: DIN 6537 K

Tolerance nominal  $\varnothing$ : h7

Number of cutting edges Z: 2

Tolerance nominal  $\varnothing$ : h7

recommended maximum drilling depth  $L_2$ : 17 mm

Overall length L: 66 mm

Shank  $\varnothing D_s$ : 6 mm

Feed f in steel  $< 900 \text{ N/mm}^2$ : 0.14 mm/rev.

### Technical description

Nominal $\varnothing D_c$	4.7 mm
Feed f in steel $< 900 \text{ N/mm}^2$	0.14 mm/rev.
Tolerance nominal $\varnothing$	h7

Overall length L	66 mm
Standard	DIN 6537 K
Flute length L <sub>c</sub>	24 mm
Shank Ø D <sub>s</sub>	6 mm
Number of cutting edges Z	2
recommended maximum drilling depth L <sub>2</sub>	17 mm
Series	HOLEX Pro Steel
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	4×D
Point angle	140 degrees
Shank	DIN 6535 HB to h6
Through-coolant	no
Machining strategy	HPC
Colour ring	green
Type of product	Jobber drill