



## HOLEX Pro Steel solid carbide drill, Whistle-Notch shank DIN 6535 HE, TiAlN, Ø DC h7 (mm or inch): 8,1 mm or inch



### Order data

Order number	122503 8,1
GTIN	4045197834683
Item class	12F

### Description

#### Version:

**Straight major cutting edges** and a **special flute profile** ensure good chip evacuation. The robust cutter geometry ensures high-performance drilling with good process reliability. A wide range of applications in steel materials thanks to a combination of tough ultra-fine grain carbide and extremely wear-resistant coating.

#### Recommendation:

##### Maximum drilling depth:

clamping slot length (see table) less  $1.5 \times \text{nominal } \varnothing$ .

##### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

Machining strategy: HPC

Standard: DIN 6537 K

Tolerance nominal  $\varnothing$ : h7

Number of cutting edges Z: 2

Tolerance nominal  $\varnothing$ : h7

recommended maximum drilling depth  $L_2$ : 34.9 mm

Overall length L: 89 mm

Shank  $\varnothing D_s$ : 10 mm

Feed f in steel  $< 900 \text{ N/mm}^2$ : 0.2 mm/rev.

### Technical description

recommended maximum drilling depth $L_2$	34.9 mm
Overall length L	89 mm
Feed f in steel $< 900 \text{ N/mm}^2$	0.2 mm/rev.

Tolerance nominal $\varnothing$	h7
Shank $\varnothing D_s$	10 mm
Standard	DIN 6537 K
Number of cutting edges Z	2
Nominal $\varnothing D_c$	8.1 mm
Flute length $L_c$	47 mm
Series	HOLEX Pro Steel
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	4×D
Point angle	140 degrees
Shank	DIN 6535 HE to h6
Through-coolant	no
Machining strategy	HPC
Colour ring	green
Type of product	Jobber drill