



HOLEX Pro Steel solid carbide drill, plain shank DIN 6535 HA, TiAlN, Ø DC h7 (mm or inch): 10,8 mm or inch



Order data

Order number	122504 10,8
GTIN	4045197826411
Item class	12F

Description

Version:

HOLEX Pro Steel:

Straight major cutting edges and a **special flute profile** ensure good chip evacuation. The robust cutter geometry ensures high-performance drilling with good process reliability. A wide range of applications in steel materials thanks to a combination of tough ultra-fine grain carbide and extremely wear-resistant coating.

Up to Ø 1.9 with 4 facets, from Ø 2 with relieved cone.

Recommendation:

Maximum drilling depth:

flute length (see table) less $1.5 \times \text{nominal } \varnothing$.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Version HB and HE supplied at the same price as HA.

Form **HB**: state **No. 122507**.

Form **HE**: state **No. 122508**.

Machining strategy: HPC

Standard: DIN 6537 K

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Tolerance nominal Ø: h7

recommended maximum drilling depth L_2 : 38.8 mm

Overall length L: 102 mm

Shank Ø D_s : 12 mm

Feed f in steel < 900 N/mm²: 0.22 mm/rev.

Technical description

Number of cutting edges Z	2
Tolerance nominal \varnothing	h7
Overall length L	102 mm
Feed f in steel < 900 N/mm ²	0.22 mm/rev.
Shank $\varnothing D_s$	12 mm
Flute length L_c	55 mm
recommended maximum drilling depth L_2	38.8 mm
Nominal $\varnothing D_c$	10.8 mm
Standard	DIN 6537 K
Series	HOLEX Pro Steel
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	4xD
Point angle	140 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Colour ring	green
Type of product	Jobber drill