

**Garant**
**Solid carbide HPC drill Weldon shank DIN 6535 HB, TiAlN, Ø DC h7: 6,9 mm**

**Order data**

Order number	122505 6,9
GTIN	4045197391650
Item class	11E

**Description**
**Version:**

Cutting chisel edge with **high centring accuracy** due to **strong core and special point geometry**. **Convex cutting edges** with honed edges and special flute profile for **short chips**, even on long chipping materials.

**Recommendation:**
**Maximum drilling depth:**

clamping slot length (see table) less 1.5×nominal Ø.

**Note:**
**NEW GENERATION AVAILABLE!**

**Recommended successor products are No. 122426 and 122436.**

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

Machining strategy: HPC

Standard: DIN 6537 K

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Tolerance nominal Ø: h7

recommended maximum drilling depth  $L_2$ : 23.7 mm

Overall length L: 79 mm

Shank Ø  $D_s$ : 8 mm

Feed f in steel < 1100 N/mm<sup>2</sup>: 0.2 mm/rev.

**Technical description**

Nominal Ø $D_c$	6.9 mm
Shank tolerance	h6
Number of cutting edges Z	2

Flute length $L_c$	34 mm
Feed $f$ in steel < 1100 N/mm <sup>2</sup>	0.2 mm/rev.
Tolerance nominal $\varnothing$	h7
Shank $\varnothing D_s$	8 mm
Overall length $L$	79 mm
Standard	DIN 6537 K
recommended maximum drilling depth $L_2$	23.7 mm
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	4×D
Point angle	140 degrees
Shank	DIN 6535 HB to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Colour ring	green
Type of product	Jobber drill