

Garant

Solid carbide HPC drill, plain shank DIN 6535 HA, DLC, Ø DC h7: 11,5 mm



Order data

Order number	122602 11,5
GTIN	4045197753151
Item class	11E

Description

Version:

DLC coating sp² of the latest generation with **low coefficient of friction** results in **outstanding chip clearance**. For **high-performance milling** of **aluminium materials**. **High alignment accuracy** and **roundness of the hole**, thanks to **6 guide chamfers**.

Size 1 - 1.5 with 4 guide chamfers.

Recommendation:

Maximum drilling depth:

flute length (see table) less 1.5×nominal Ø.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 122603**.

Form **HE**: order with **No. 122602 + 129100HE**.

Standard: DIN 6537

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Tolerance nominal Ø: h7

recommended maximum drilling depth L_2 : 53.8 mm

Overall length L: 118 mm

Shank Ø D_s : 12 mm

Feed f in aluminium short-chipping: 0.55 mm/rev.

Technical description

Overall length L	118 mm
Shank Ø D_s	12 mm

Feed f in aluminium short-chipping	0.55 mm/rev.
Nominal $\varnothing D_c$	11.5 mm
Tolerance nominal \varnothing	h7
Standard	DIN 6537
Shank tolerance	h6
Number of cutting edges Z	2
Flute length L_c	71 mm
recommended maximum drilling depth L_2	53.8 mm
Coating	DLC
Tool material	solid carbide
Drill depth up to	6xD
Type	W
Point angle	135 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	yellow
Type of product	Jobber drill

Services

Shank grinding Type HE	129100 HE
------------------------	-----------