

Garant
Solid carbide HPC drill Weldon shank DIN 6535 HB, DLC, Ø DC h7: 11,5 mm

Order data

Order number	122603 11,5
GTIN	4045197758279
Item class	11E

Description
Version:

DLC coating sp^2 of the latest generation with **low coefficient of friction** results in **outstanding chip clearance**. For **high-performance milling** of **aluminium materials**. **High roundness** and **alignment accuracy of the deep hole**, thanks to **6 guide chamfers**.

Recommendation:
Maximum drilling depth:

clamping slot length (see table) less $1.5 \times$ nominal \varnothing .

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$

Standard: DIN 6537

Tolerance nominal \varnothing : h7

Number of cutting edges Z: 2

Tolerance nominal \varnothing : h7

recommended maximum drilling depth L_2 : 53.8 mm

Overall length L: 118 mm

Shank $\varnothing D_s$: 12 mm

Feed f in aluminium short-chipping: 0.55 mm/rev.

Technical description

Shank $\varnothing D_s$	12 mm
Number of cutting edges Z	2
Nominal $\varnothing D_c$	11.5 mm
Flute length L_c	71 mm
Overall length L	118 mm

Feed f in aluminium short-chipping	0.55 mm/rev.
Standard	DIN 6537
Tolerance nominal \varnothing	h7
Shank tolerance	h6
recommended maximum drilling depth L ₂	53.8 mm
Coating	DLC
Tool material	solid carbide
Drill depth up to	6xD
Type	W
Point angle	135 degrees
Shank	DIN 6535 HB to h6
Through-coolant	Yes, with 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	yellow
Type of product	Jobber drill