

Garant
Solid carbide HPC drill Weldon shank DIN 6535 HB, DLC, Ø DC h7: 15,1 mm

Order data

Order number	122603 15,1
GTIN	4045197758408
Item class	11E

Description
Version:

DLC coating sp² of the latest generation with **low coefficient of friction** results in **outstanding chip clearance**. For **high-performance milling** of **aluminium materials**. **High roundness** and **alignment accuracy of the deep hole**, thanks to **6 guide chamfers**.

Recommendation:
Maximum drilling depth:

clamping slot length (see table) less 1.5×nominal Ø.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$

Standard: DIN 6537

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Tolerance nominal Ø: h7

recommended maximum drilling depth L_2 : 60.4 mm

Overall length L: 133 mm

Shank Ø D_s : 16 mm

Feed f in aluminium short-chipping: 0.65 mm/rev.

Technical description

Flute length L_c	83 mm
Tolerance nominal Ø	h7
Overall length L	133 mm
Shank tolerance	h6
Nominal Ø D_c	15.1 mm

Number of cutting edges Z	2
Feed f in aluminium short-chipping	0.65 mm/rev.
Shank $\varnothing D_s$	16 mm
Standard	DIN 6537
recommended maximum drilling depth L_2	60.4 mm
Coating	DLC
Tool material	solid carbide
Drill depth up to	6xD
Type	W
Point angle	135 degrees
Shank	DIN 6535 HB to h6
Through-coolant	Yes, with 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	yellow
Type of product	Jobber drill