

Garant
Solid carbide HPC drill Weldon shank DIN 6535 HB, DLC, Ø DC h7: 3,25 mm

Order data

Order number	122603 3,25
GTIN	4045197757494
Item class	11E

Description
Version:

DLC coating sp^2 of the latest generation with **low coefficient of friction** results in **outstanding chip clearance**. For **high-performance milling** of **aluminium materials**. **High roundness** and **alignment accuracy of the deep hole**, thanks to **6 guide chamfers**.

Recommendation:
Maximum drilling depth:

clamping slot length (see table) less $1.5 \times$ nominal \varnothing .

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$

Standard: DIN 6537

Tolerance nominal \varnothing : h7

Number of cutting edges Z: 2

Tolerance nominal \varnothing : h7

recommended maximum drilling depth L_2 : 23.2 mm

Overall length L: 66 mm

Shank $\varnothing D_s$: 6 mm

Feed f in aluminium short-chipping: 0.35 mm/rev.

Technical description

Nominal $\varnothing D_c$	3.25 mm
Shank $\varnothing D_s$	6 mm
Shank tolerance	h6
Feed f in aluminium short-chipping	0.35 mm/rev.
Tolerance nominal \varnothing	h7

Number of cutting edges Z	2
Standard	DIN 6537
Overall length L	66 mm
Flute length L _c	28 mm
recommended maximum drilling depth L ₂	23.2 mm
Coating	DLC
Tool material	solid carbide
Drill depth up to	6×D
Type	W
Point angle	135 degrees
Shank	DIN 6535 HB to h6
Through-coolant	Yes, with 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	yellow
Type of product	Jobber drill