

Garant

Solid carbide HPC drill Weldon shank DIN 6535 HB, DLC, Ø DC h7: 5,6 mm



Order data

Order number	122603 5,6
GTIN	4045197757753
Item class	11E

Description

Version:

DLC coating sp² of the latest generation with **low coefficient of friction** results in **outstanding chip clearance**. For **high-performance milling** of **aluminium materials**. **High roundness** and **alignment accuracy of the deep hole**, thanks to **6 guide chamfers**.

Recommendation:

Maximum drilling depth:

clamping slot length (see table) less 1.5×nominal Ø.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$

Standard: DIN 6537

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Tolerance nominal Ø: h7

recommended maximum drilling depth L_2 : 35.6 mm

Overall length L: 82 mm

Shank Ø D_s : 6 mm

Feed f in aluminium short-chipping: 0.45 mm/rev.

Technical description

Standard	DIN 6537
Shank Ø D_s	6 mm
Shank tolerance	h6
Tolerance nominal Ø	h7
Number of cutting edges Z	2

Feed f in aluminium short-chipping	0.45 mm/rev.
Nominal $\varnothing D_c$	5.6 mm
Overall length L	82 mm
Flute length L_c	44 mm
recommended maximum drilling depth L_2	35.6 mm
Coating	DLC
Tool material	solid carbide
Drill depth up to	6xD
Type	W
Point angle	135 degrees
Shank	DIN 6535 HB to h6
Through-coolant	Yes, with 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	yellow
Type of product	Jobber drill