

Garant
Solid carbide HPC drill plain shank DIN 6535 HA, DLC, Ø DC p6: 2,3 mm

Order data

| | |
|--------------|---------------|
| Order number | 122606 2,3 |
| GTIN | 4045197567949 |
| Item class | 11E |

Description
Version:

Spiral fluted, with **6 guide chamfers** and internal cooling channels.

New generation of high performance pilot drills in the HPC range.

With **140° point angle** and special **p6 cutting edge tolerance** for optimum generation of a pilot hole. High alignment accuracy and **roundness of the pilot hole**.

Recommendation:
Maximum drilling depth:

Flute length (see table) less 1.5×nominal Ø.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

For deep-hole drilling deeper than 16×D a pilot hole is recommended, and for deep-hole drilling from 20×D to 30×D it is essential. **The generation of a pilot hole improves process reliability.**

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 122608**.

Form **HE**: order with **No. 122606 + 129100HE**.

Standard: DIN 6537

Tolerance nominal Ø: p6

Number of cutting edges Z: 2

Tolerance nominal Ø: p6

recommended maximum drilling depth L_2 : 17.6 mm

Overall length L: 57 mm

Shank Ø D_s : 4 mm

Feed f in aluminium short-chipping: 0.18 mm/rev.

Technical description

| | |
|--------------------|-------|
| Flute length L_c | 21 mm |
|--------------------|-------|

| | |
|--|-------------------|
| Nominal $\varnothing D_c$ | 2.3 mm |
| Feed f in aluminium short-chipping | 0.18 mm/rev. |
| Number of cutting edges Z | 2 |
| Shank tolerance | h6 |
| Tolerance nominal \varnothing | p6 |
| Shank $\varnothing D_s$ | 4 mm |
| Overall length L | 57 mm |
| Standard | DIN 6537 |
| recommended maximum drilling depth L_2 | 17.6 mm |
| Coating | DLC |
| Tool material | Solid carbide |
| Drill depth up to | 6×D |
| Type | W |
| Point angle | 140 degrees |
| Shank | DIN 6535 HA to h6 |
| Through-coolant | yes, with 25 bar |
| Machining strategy | HPC |
| Semi-Standard | yes |
| Colour ring | yellow |
| Type of product | Jobber drill |