

Solid carbide HPC drill plain shank DIN 6535 HA, DLC, Ø DC p6: 9,8 mm



Order data

Order number	122606 9,8
GTIN	4045197568274
Item class	11E

Description

Version:

Spiral fluted, with 6 guide chamfers and internal cooling channels.

New generation of high performance pilot drills in the HPC range.

With **140° point angle** and special **p6 cutting edge tolerance** for optimum generation of a pilot hole. High alignment accuracy and **roundness of the pilot hole.**

Recommendation:

Maximum drilling depth:

Flute length (see table) less $1.5 \times \text{nominal } \emptyset$.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

For deep-hole drilling deeper than $16 \times D$ a pilot hole is recommended, and for deep-hole drilling from $20 \times D$ to $30 \times D$ it is essential. **The generation of a pilot hole improves process reliability.**

Form HB and HE supplied at the same price as HA.

Form HB: order with No. 122608.

Form **HE**: order with **No. 122606 + 129100HE**.

Standard: DIN 6537 Tolerance nominal Ø: p6

Number of cutting edges Z: 2

Tolerance nominal Ø: p6

recommended maximum drilling depth L₂: 46.3 mm

Overall length L: 103 mm Shank Ø D_s: 10 mm

Feed f in aluminium short-chipping: 0.44 mm/rev.

Technical description

Flute length L _c	61 mm
-----------------------------	-------



Shank tolerance	h6
Nominal Ø D _c	9.8 mm
Number of cutting edges Z	2
Feed f in aluminium short-chipping	0.44 mm/rev.
Tolerance nominal Ø	р6
Shank Ø D _s	10 mm
Overall length L	103 mm
Standard	DIN 6537
recommended maximum drilling depth L_2	46.3 mm
Coating	DLC
Tool material	Solid carbide
Drill depth up to	6×D
Type	W
Point angle	140 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	yellow
Type of product	Jobber drill

Shank grinding Type HE

Services

129100 HE