

**HOLEX**
**Solid carbide high performance drill plain shank DIN 6535 HA, TiN, Ø DC h7  
(mm or inch): 9,6 mm or inch**

**Order data**

|              |               |
|--------------|---------------|
| Order number | 122630 9,6    |
| GTIN         | 4045197054173 |
| Item class   | 12E           |

**Description**
**Version:**

Cutting chisel edge with **high centring accuracy** due to **strong core and special point geometry**.

**Straight major cutting edges** with slightly honed edges and special flute profile produce **short chips**.

**Recommendation:**
**Maximum drilling depth:**

Flute length (see table) less 1.5×nominal Ø.

**Note:**

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 122635**.

Form **HE**: order with **No. 122640**.

**NEW GENERATION AVAILABLE!**

**Recommended successor product is No. 122776.**

Standard: DIN 6537

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Semi-Standard: yes

Tolerance nominal Ø: h7

recommended maximum drilling depth  $L_2$ : 46.6 mm

Overall length L: 103 mm

Shank Ø  $D_s$ : 10 mm

Feed f in steel < 900 N/mm<sup>2</sup>: 0.22 mm/rev.

**Technical description**

|  |                   |
|--|-------------------|
| Flute length $L_c$                       | 61 mm             |
| Number of cutting edges Z                | 2                 |
| Feed f in steel < 900 N/mm <sup>2</sup>  | 0.22 mm/rev.      |
| Nominal $\varnothing D_c$                | 9.6 mm            |
| Shank tolerance                          | h6                |
| Tolerance nominal $\varnothing$          | h7                |
| Shank $\varnothing D_s$                  | 10 mm             |
| Overall length L                         | 103 mm            |
| Standard                                 | DIN 6537          |
| recommended maximum drilling depth $L_2$ | 46.6 mm           |
| Semi-Standard                            | yes               |
| Coating                                  | TiN               |
| Tool material                            | Solid carbide     |
| Drill depth up to                        | 6×D               |
| Point angle                              | 140 degrees       |
| Shank                                    | DIN 6535 HA to h6 |
| Through-coolant                          | yes, with 25 bar  |
| Colour ring                              | green             |
| Type of product                          | Jobber drill      |