



## Solid carbide high performance drill Whistle-Notch shank DIN 6535 HE, TiN, Ø DC h7: 8,7 mm



### Order data

Order number	122640 8,7
GTIN	4045197395658
Item class	12E

### Description

#### Version:

Cutting chisel edge with **high centring accuracy** due to **strong core and special point geometry**.

**Straight major cutting edges** with slightly honed edges and special flute profile produce **short chips**.

#### Recommendation:

#### Maximum drilling depth:

clamping slot length (see table) less 1.5×nominal Ø.

#### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

#### NEW GENERATION AVAILABLE!

**Recommended successor product is No. 122778.**

Through-coolant: yes, with 25 bar

Standard: DIN 6537

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Tolerance nominal Ø: h7

recommended maximum drilling depth  $L_2$ : 48 mm

Overall length L: 103 mm

Shank Ø  $D_s$ : 10 mm

Feed f in steel < 900 N/mm<sup>2</sup>: 0.18 mm/rev.

### Technical description

Feed f in steel < 900 N/mm <sup>2</sup>	0.18 mm/rev.
Flute length $L_c$	61 mm

Number of cutting edges Z	2
Shank tolerance	h6
Nominal $\varnothing D_c$	8.7 mm
Tolerance nominal $\varnothing$	h7
Shank $\varnothing D_s$	10 mm
Overall length L	103 mm
Standard	DIN 6537
recommended maximum drilling depth $L_2$	48 mm
Coating	TiN
Tool material	Solid carbide
Drill depth up to	6xD
Point angle	140 degrees
Shank	DIN 6535 HE to h6
Through-coolant	yes, with 25 bar
Colour ring	green
Type of product	Jobber drill