

## Garant

### Diabolo solid carbide HPC drill, plain shank DIN 6535 HA, TiAlN, Ø DC h7: 4,3 mm



#### Order data

Order number	122651 4,3
GTIN	4045197970091
Item class	11E

#### Description

##### Version:

Cutting chisel edge with **high centring accuracy** due to **strong core and special point geometry**. **Convex major cutting edges** with **defined honed edge** ensure the drill has high stability and maximum load capacity.

**Special multi-nano layer coating** for drilling in hardened steels.

##### Recommendation:

##### Maximum drilling depth:

Flute length (see table) less 1.5×nominal Ø.

##### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 122642 / 122652**.

Form **HE**: order with **No. 122641 / 122651 + 129100HE**.

Standard: DIN 6537

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Tolerance nominal Ø: h7

recommended maximum drilling depth  $L_2$ : 29.6 mm

Overall length L: 74 mm

Shank Ø  $D_s$ : 6 mm

Feed f in steel < 60 HRC: 0.04 mm/rev.

#### Technical description

Nominal Ø $D_c$	4.3 mm
Number of cutting edges Z	2

Tolerance nominal $\varnothing$	h7
recommended maximum drilling depth $L_2$	29.6 mm
Feed $f$ in steel < 60 HRC	0.04 mm/rev.
Standard	DIN 6537
Overall length $L$	74 mm
Flute length $L_c$	36 mm
Shank $\varnothing D_s$	6 mm
Series	Diabolo
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	6xD
Type	H
Point angle	140 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	red
Type of product	Jobber drill

## Services

Shank grinding Type HE	129100 HE
------------------------	-----------