Garant

Solid carbide HPC drill plain shank DIN 6535 HA, TiAIN, Ø DC m6 (Ø DC X = h7) (mm or inch): 14,1 mm or inch

denor

Order data

Order number	122659 14,1
GTIN	4045197582973
Item class	11E

Description

Version:

Cutting chisel edge with **high centring accuracy** due to **strong core and special point geometry.** High roundness and alignment accuracy of the deep hole, thanks to **4 guide chamfers.** Outstanding chip evacuation due to **4 internal cooling channels** from Ø 3.8 mm. Up to 3.7 mm Ø with 2 internal cooling channels. **Straight major cutting edges** with honed edges and special flute profile for **short chips**, even on long chipping materials.

Recommendation: Maximum drilling depth:

Flute length (see table) less $1.5 \times nominal \emptyset$.

Attention:

Sizes **ending with X** = cutter Ø tolerance **h7**.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$. Form HB and HE supplied at the same price as HA. Form **HB**: order with **No. 122661**. Form **HE**: order with **No. 122659 + 129100HE**. Standard: DIN 6537 Tolerance nominal Ø: m6 Number of cutting edges Z: 2 Tolerance nominal Ø: m6 recommended maximum drilling depth L_2 : 61.9 mm Overall length L: 133 mm Shank Ø D_s: 16 mm Feed f in stainless steel > 900 N/mm²: 0.2 mm/rev.

Technical description

roup 🖈

Data sheet

h6
14.1 mm
2
0.2 mm/rev.
83 mm
тб
16 mm
133 mm
DIN 6537
61.9 mm
TiAIN
Solid carbide
6×D
140 degrees
right-hand
DIN 6535 HA to h6
yes, with 25 bar
HPC
yes
blue
Jobber drill

Services