

Garant

**Solid carbide HPC drill plain shank DIN 6535 HA, TiAlN, Ø DC m6 (Ø DC X = h7)
(mm or inch): 14,3 mm or inch**



Order data

Order number	122659 14,3
GTIN	4045197743657
Item class	11E

Description

Version:

Cutting chisel edge with **high centring accuracy** due to **strong core and special point geometry**. High roundness and alignment accuracy of the deep hole, thanks to **4 guide chamfers**. Outstanding chip evacuation due to **4 internal cooling channels** from Ø 3.8 mm. Up to 3.7 mm Ø with 2 internal cooling channels. **Straight major cutting edges** with honed edges and special flute profile for **short chips**, even on long chipping materials.

Recommendation:

Maximum drilling depth:

Flute length (see table) less 1.5×nominal Ø.

Attention:

Sizes **ending with X** = cutter Ø tolerance **h7**.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 122661**.

Form **HE**: order with **No. 122659 + 129100HE**.

Standard: DIN 6537

Tolerance nominal Ø: m6

Number of cutting edges Z: 2

Tolerance nominal Ø: m6

recommended maximum drilling depth L_2 : 61.6 mm

Overall length L: 133 mm

Shank Ø D_s : 16 mm

Feed f in stainless steel > 900 N/mm²: 0.2 mm/rev.

Technical description

Number of cutting edges Z	2
Shank tolerance	h6
Nominal $\varnothing D_c$	14.3 mm
Standard	DIN 6537
Tolerance nominal \varnothing	m6
Shank $\varnothing D_s$	16 mm
Feed f in stainless steel > 900 N/mm ²	0.2 mm/rev.
Flute length L _c	83 mm
Overall length L	133 mm
recommended maximum drilling depth L ₂	61.6 mm
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	6×D
Point angle	140 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	blue
Type of product	Jobber drill

Services

Shank grinding Type HE	129100 HE
------------------------	-----------