

Garant

Solid carbide HPC drill Weldon shank DIN 6535 HB, TiAlN, Ø DC m6 (Ø DC X = h7): 12,55 mm



Order data

| | |
|--------------|---------------|
| Order number | 122661 12,55 |
| GTIN | 4045197583581 |
| Item class | 11E |

Description

Version:

Cutting chisel edge with **high centring accuracy** due to **strong core and special point geometry**. High roundness and alignment accuracy of the deep hole, thanks to **4 guide chamfers**. Outstanding chip evacuation due to **4 internal cooling channels** from Ø 3.8 mm. Up to 3.7 mm Ø with 2 internal cooling channels. **Straight major cutting edges** with honed edges and special flute profile for **short chips**, even on long chipping materials.

Recommendation:

Maximum drilling depth:

Flute length (see table) less 1.5×nominal Ø.

Attention:

Sizes **ending with X** = cutter Ø tolerance **h7**.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Machining strategy: HPC

Standard: DIN 6537

Tolerance nominal Ø: m6

Number of cutting edges Z: 2

Semi-Standard: yes

Tolerance nominal Ø: m6

recommended maximum drilling depth L_2 : 58.2 mm

Overall length L: 124 mm

Shank Ø D_s : 14 mm

Feed f in stainless steel > 900 N/mm²: 0.2 mm/rev.

Technical description

| | |
|---|-------------------|
| Shank tolerance | h6 |
| Number of cutting edges Z | 2 |
| Nominal $\varnothing D_c$ | 12.55 mm |
| Feed f in stainless steel > 900 N/mm ² | 0.2 mm/rev. |
| Flute length L _c | 77 mm |
| Tolerance nominal \varnothing | m6 |
| Shank $\varnothing D_s$ | 14 mm |
| Overall length L | 124 mm |
| Standard | DIN 6537 |
| recommended maximum drilling depth L ₂ | 58.2 mm |
| Semi-Standard | yes |
| Coating | TiAlN |
| Tool material | Solid carbide |
| Drill depth up to | 6×D |
| Point angle | 140 degrees |
| Shank | DIN 6535 HB to h6 |
| Through-coolant | yes, with 25 bar |
| Machining strategy | HPC |
| Colour ring | blue |
| Type of product | Jobber drill |