

## Garant

**Solid carbide HPC drill Weldon shank DIN 6535 HB, TiAlN, Ø DC m6 (Ø DC X = h7): 9,35 mm**



### Order data

Order number	122661 9,35
GTIN	4045197583369
Item class	11E

### Description

#### Version:

Cutting chisel edge with **high centring accuracy** due to **strong core and special point geometry**. High roundness and alignment accuracy of the deep hole, thanks to **4 guide chamfers**. Outstanding chip evacuation due to **4 internal cooling channels** from Ø 3.8 mm. Up to 3.7 mm Ø with 2 internal cooling channels. **Straight major cutting edges** with honed edges and special flute profile for **short chips**, even on long chipping materials.

#### Recommendation:

##### Maximum drilling depth:

Flute length (see table) less 1.5×nominal Ø.

##### Attention:

Sizes **ending with X** = cutter Ø tolerance **h7**.

##### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

Standard: DIN 6537

Tolerance nominal Ø: m6

Number of cutting edges Z: 2

Tolerance nominal Ø: m6

recommended maximum drilling depth  $L_2$ : 47 mm

Overall length L: 103 mm

Shank Ø  $D_s$ : 10 mm

Feed f in stainless steel > 900 N/mm<sup>2</sup>: 0.15 mm/rev.

### Technical description

Number of cutting edges Z	2
Nominal Ø $D_c$	9.35 mm

Flute length $L_c$	61 mm
Feed $f$ in stainless steel $> 900 \text{ N/mm}^2$	0.15 mm/rev.
Shank tolerance	h6
Tolerance nominal $\varnothing$	m6
Shank $\varnothing D_s$	10 mm
Overall length $L$	103 mm
Standard	DIN 6537
recommended maximum drilling depth $L_2$	47 mm
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	6xD
Point angle	140 degrees
Cutting direction	right-hand
Shank	DIN 6535 HB to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	blue
Type of product	Jobber drill