

**HOLEX**
**Solid carbide high performance drill plain shank DIN 6535 HA, TiAlN, Ø DC m7: 9,3 mm**

**Order data**

Order number	122664 9,3
GTIN	4045197421685
Item class	12E

**Description**
**Version:**

Cutting chisel edge with **high centring accuracy** due to **strong core and special point geometry**. **Straight major cutting edges** with slightly honed edges and special flute profile produce **short chips**.

**Recommendation:**
**Maximum drilling depth:**

flute length (see table) less 1.5×nominal Ø.

**Note:**

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 122666**.

Form **HE**: order with **No. 122668**.

Through-coolant: yes, with 25 bar

Standard: DIN 6537

Tolerance nominal Ø: m7

Number of cutting edges Z: 2

Tolerance nominal Ø: m7

recommended maximum drilling depth  $L_2$ : 47.1 mm

Overall length L: 103 mm

Shank Ø  $D_s$ : 10 mm

Feed f in stainless steel < 900 N/mm<sup>2</sup>: 0.12 mm/rev.

**Technical description**

Flute length $L_c$	61 mm
Feed f in stainless steel < 900 N/mm <sup>2</sup>	0.12 mm/rev.

Nominal $\varnothing D_c$	9.3 mm
Number of cutting edges Z	2
Shank tolerance	h6
Tolerance nominal $\varnothing$	m7
Shank $\varnothing D_s$	10 mm
Overall length L	103 mm
Standard	DIN 6537
recommended maximum drilling depth $L_2$	47.1 mm
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	6xD
Point angle	140 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Colour ring	blue
Type of product	Jobber drill