

**HOLEX**

**Solid carbide high performance drill Whistle-Notch shank DIN 6535 HE, TiAlN,  
Ø DC m7: 6,5 mm**



## Order data

Order number	122668 6,5
GTIN	4045197428790
Item class	12E

## Description

### Version:

Cutting chisel edge with **high centring accuracy** due to **strong core and special point geometry**. **Straight major cutting edges** with slightly honed edges and special flute profile produce **short chips**.

### Recommendation:

#### Maximum drilling depth:

Flute length (see table) less 1.5×nominal Ø.

### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

Through-coolant: yes, with 25 bar

Standard: DIN 6537

Tolerance nominal Ø: m7

Number of cutting edges Z: 2

Tolerance nominal Ø: m7

recommended maximum drilling depth  $L_2$ : 43.3 mm

Overall length L: 91 mm

Shank Ø  $D_s$ : 8 mm

Feed f in stainless steel < 900 N/mm<sup>2</sup>: 0.1 mm/rev.

## Technical description

Flute length $L_c$	53 mm
Shank tolerance	h6
Feed f in stainless steel < 900 N/mm <sup>2</sup>	0.1 mm/rev.
Nominal Ø $D_c$	6.5 mm

Number of cutting edges Z	2
Tolerance nominal $\varnothing$	m7
Shank $\varnothing D_s$	8 mm
Overall length L	91 mm
Standard	DIN 6537
recommended maximum drilling depth $L_2$	43.3 mm
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	6xD
Point angle	140 degrees
Shank	DIN 6535 HE to h6
Through-coolant	yes, with 25 bar
Colour ring	blue
Type of product	Jobber drill