

## Garant

**Solid carbide HPC drill type FS plain shank DIN 6535 HA, TiAlN, Ø DC h7: 11,5 mm**



### Order data

Order number	122670 11,5
GTIN	4045197056979
Item class	11E

### Description

#### Version:

**Particularly strong** due to strengthened core and **special profile**. Special point geometry. **High concentricity** and **long tool life**.

**High bore quality.**

#### Recommendation:

#### Maximum drilling depth:

flute length (see table) less  $1.5 \times$  nominal  $\varnothing$ .

#### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 122675**.

Form **HE**: order with **No. 122670 + 129100HE**.

Standard: DIN 6537

Tolerance nominal  $\varnothing$ : h7

Number of cutting edges Z: 2

Tolerance nominal  $\varnothing$ : h7

recommended maximum drilling depth  $L_2$ : 53.8 mm

Overall length L: 118 mm

Shank  $\varnothing D_s$ : 12 mm

Feed f in titanium  $> 850 \text{ N/mm}^2$ : 0.12 mm/rev.

### Technical description

Number of cutting edges Z	2
Flute length $L_c$	71 mm

Nominal $\varnothing D_c$	11.5 mm
Shank tolerance	h6
Feed f in titanium > 850 N/mm <sup>2</sup>	0.12 mm/rev.
Tolerance nominal $\varnothing$	h7
Shank $\varnothing D_s$	12 mm
Overall length L	118 mm
Standard	DIN 6537
recommended maximum drilling depth L <sub>2</sub>	53.8 mm
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	6×D
Type	FS
Point angle	140 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	pink
Type of product	Jobber drill

## Services

Shank grinding Type HE	129100 HE
------------------------	-----------