

## Garant

**Solid carbide HPC drill type FS Weldon shank DIN 6535 HB, TiAlN, Ø DC h7:  
10,8 mm**



### Order data

Order number	122675 10,8
GTIN	4045197398314
Item class	11E

### Description

#### Version:

**Particularly strong** due to strengthened core and **special profile**. Special point geometry.  
**High concentricity** and **long tool life**.

**Precision drilling qualities.**

#### Recommendation:

#### Maximum drilling depth:

Flute length (see table) less 1.5×nominal Ø.

#### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

Standard: DIN 6537

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Tolerance nominal Ø: h7

recommended maximum drilling depth  $L_2$ : 54.8 mm

Overall length L: 118 mm

Shank Ø  $D_s$ : 12 mm

Feed f in titanium > 850 N/mm<sup>2</sup>: 0.12 mm/rev.

### Technical description

Nominal Ø $D_c$	10.8 mm
Flute length $L_c$	71 mm
Shank tolerance	h6
Feed f in titanium > 850 N/mm <sup>2</sup>	0.12 mm/rev.

Number of cutting edges Z	2
Tolerance nominal $\varnothing$	h7
Shank $\varnothing D_s$	12 mm
Overall length L	118 mm
Standard	DIN 6537
recommended maximum drilling depth $L_2$	54.8 mm
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	6xD
Type	FS
Point angle	140 degrees
Shank	DIN 6535 HB to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	pink
Type of product	Jobber drill