## Garant

# GARANT Master Steel FEED solid carbide drill, plain shank DIN 6535 HA, TIAIN, Ø DC h7: 10,6 mm or inch

dame III

## Order data

Order number	122725 10,6
GTIN	4045197789556
Item class	11E

## Description

#### Version:

**3-flute drill**, specially developed for use at **very high feed rates**. Outstandingly suitable for **machines with high installed power** and stable operating conditions.

- Special cutter geometry with stable cutting edges and large clearance at the centre enables very high feed rates.
- The patented tip is optimised for chip flow and generates low cutting pressure with good chip breakage.
- With 145° tip angle for low burr formation when drilling through holes.
- The sector-leading technology of the chisel edge guarantees optimum self-centring

**behaviour** and permits spot drilling on irregular surfaces. 3 guide chamfers guarantee a stable exit from the hole and an exact roundness of the hole.

### **Recommendation:**

#### Maximum drilling depth:

flute length (see table) less  $1.5 \times nominal \emptyset$ .

#### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ . Form HB and HE supplied at the same price as HA. Form **HB**: order with **No. 122726**. Form **HE**: order with **No. 122725 + 129100HE**. Machining strategy: HPC Standard: DIN 6537 Tolerance nominal  $\emptyset$ : h7 Number of cutting edges Z: 3 Semi-Standard: yes Tolerance nominal  $\emptyset$ : h7 recommended maximum drilling depth  $L_2$ : 55.1 mm Overall length L: 118 mm

## Data sheet

Shank  $\emptyset$  D<sub>s</sub>: 12 mm Feed f in steel < 1100 N/mm<sup>2</sup>: 0.5 mm/rev.

# **Technical description**

2	
Feed f in steel < 1100 N/mm <sup>2</sup>	0.5 mm/rev.
Flute length L <sub>c</sub>	71 mm
Nominal Ø D <sub>c</sub>	10.6 mm
Number of cutting edges Z	3
Overall length L	118 mm
Standard	DIN 6537
Shank $\emptyset$ D <sub>s</sub>	12 mm
Tolerance nominal Ø	h7
recommended maximum drilling depth $L_2$	55.1 mm
Semi-Standard	yes
Series	GARANT Master Steel
Series Coating	GARANT Master Steel TiAlN
Coating	TiAIN
Coating Tool material	TiAIN solid carbide
Coating Tool material Drill depth up to	TiAlN solid carbide 6×D
Coating Tool material Drill depth up to Point angle	TiAlN solid carbide 6×D 145 degrees
Coating Tool material Drill depth up to Point angle Shank	TiAlN solid carbide 6×D 145 degrees DIN 6535 HA to h6
Coating Tool material Drill depth up to Point angle Shank Through-coolant	TiAlN solid carbide $6 \times D$ 145 degrees DIN 6535 HA to h6 yes, with 25 bar
Coating Tool material Drill depth up to Point angle Shank Through-coolant Machining strategy	TiAlN solid carbide $6 \times D$ 145 degrees DIN 6535 HA to h6 yes, with 25 bar HPC

# Services

Shank grinding Type HE

129100 HE