Garant

GARANT Master Steel FEED solid carbide drill, plain shank DIN 6535 HA, TIAIN, Ø DC h7 (mm or inch): 14,2 mm or inch



Order data

Order number	122725 14,2
GTIN	4045197789785
Item class	11E

Description

Version:

3-flute drill, specially developed for use at **very high feed rates**. Outstandingly suitable for **machines with high installed power** and stable operating conditions.

- Special cutter geometry with stable cutting edges and large clearance at the centre enables very high feed rates.
- The patented tip is optimised for chip flow and generates low cutting pressure with good chip breakage.
- With 145° tip angle for low burr formation when drilling through holes.
- The sector-leading technology of the chisel edge guarantees optimum self-centring

behaviour and permits spot drilling on irregular surfaces. 3 guide chamfers guarantee a stable exit from the hole and an exact roundness of the hole.

Recommendation:

Maximum drilling depth:

flute length (see table) less $1.5 \times nominal \emptyset$.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$. Form HB and HE supplied at the same price as HA. Form **HB**: order with **No. 122726**. Form **HE**: order with **No. 122725 + 129100HE**. Standard: DIN 6537 Tolerance nominal Ø: h7 Number of cutting edges Z: 3 Tolerance nominal Ø: h7 recommended maximum drilling depth L_2 : 61.7 mm Overall length L: 133 mm Shank Ø D_s: 16 mm Feed f in steel < 1100 N/mm²: 0.61 mm/rev.

Data sheet

Technical description

Number of cutting edges Z	3
Standard	DIN 6537
Overall length L	133 mm
Tolerance nominal Ø	h7
Nominal Ø D _c	14.2 mm
Shank Ø D _s	16 mm
Flute length L _c	83 mm
Feed f in steel < 1100 N/mm ²	0.61 mm/rev.
recommended maximum drilling depth L_2	61.7 mm
Series	GARANT Master Steel
Coating	TiAlN
Tool material	solid carbide
Drill depth up to	6×D
Point angle	145 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	green
Type of product	Jobber drill

Services

Shank grinding Type HE	129100 HE
------------------------	-----------