

GARANT Master Steel FEED solid carbide drill, plain shank DIN 6535 HA, TiAlN, Ø DC h7 (mm or inch): 17 mm or inch



Order data

Order number	122725 17
GTIN	4045197789891
Item class	11E

Description

Version:

- **3-flute drill**, specially developed for use at **very high feed rates**. Outstandingly suitable for **machines with high installed power** and stable operating conditions.
- Special cutter geometry with stable cutting edges and large clearance at the centre enables very high feed rates.
- The patented tip is optimised for chip flow and generates low cutting pressure with good chip breakage.
- · With 145° tip angle for low burr formation when drilling through holes.

The sector-leading technology of the chisel edge guarantees optimum self-centring behaviour and permits spot drilling on irregular surfaces. 3 guide chamfers guarantee a stable exit from the hole and an exact roundness of the hole.

Recommendation:

Maximum drilling depth:

flute length (see table) less $1.5 \times \text{nominal } \emptyset$.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Form HB and HE supplied at the same price as HA.

Form HB: order with No. 122726.

Form **HE**: order with **No. 122725 + 129100HE**.

Standard: DIN 6537 Tolerance nominal Ø: h7 Number of cutting edges Z: 3

Tolerance nominal Ø: h7

recommended maximum drilling depth L₂: 67.5 mm

Overall length L: 143 mm Shank Ø D_s: 18 mm

Feed f in steel $< 1100 \text{ N/mm}^2$: 0.66 mm/rev.

Technical description

Standard	DIN 6537
Flute length L _c	93 mm
Tolerance nominal Ø	h7
Nominal Ø D _c	17 mm
Feed f in steel < 1100 N/mm ²	0.66 mm/rev.
Number of cutting edges Z	3
Overall length L	143 mm
Shank Ø D _s	18 mm
recommended maximum drilling depth L ₂	67.5 mm
Series	GARANT Master Steel
Coating	TiAIN
Tool material	solid carbide
Drill depth up to	6×D
Point angle	145 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	green
Type of product	Jobber drill

Services

Shank grinding Type HE 129100 HE	Shank grinding Type HE	129100 HE
----------------------------------	------------------------	-----------