

# GARANT Master Steel FEED solid carbide drill, plain shank DIN 6535 HA, TiAlN, Ø DC h7: 19,2 mm or inch



#### Order data

Order number	122725 19,2
GTIN	4045197789983
Item class	11E

#### **Description**

#### Version:

- **3-flute drill**, specially developed for use at **very high feed rates**. Outstandingly suitable for **machines with high installed power** and stable operating conditions.
- Special cutter geometry with stable cutting edges and large clearance at the centre enables very high feed rates.
- The patented tip is optimised for chip flow and generates low cutting pressure with good chip breakage.
- · With 145° tip angle for low burr formation when drilling through holes.

The sector-leading technology of the chisel edge guarantees optimum self-centring behaviour and permits spot drilling on irregular surfaces. 3 guide chamfers guarantee a stable exit from the hole and an exact roundness of the hole.

#### **Recommendation:**

#### **Maximum drilling depth:**

flute length (see table) less  $1.5 \times \text{nominal } \emptyset$ .

#### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

Form HB and HE supplied at the same price as HA.

Form HB: order with No. 122726.

Form **HE:** order with **No. 122725 + 129100HE**.

Machining strategy: HPC

Standard: DIN 6537

Tolerance nominal Ø: h7

Number of cutting edges Z: 3

Semi-Standard: yes

Tolerance nominal Ø: h7

recommended maximum drilling depth L₂: 72.2 mm

Overall length L: 153 mm

Shank Ø D<sub>s</sub>: 20 mm

Feed f in steel < 1100 N/mm<sup>2</sup>: 0.69 mm/rev.

## **Technical description**

Number of cutting edges Z	3
Flute length L <sub>c</sub>	101 mm
Nominal Ø D <sub>c</sub>	19.2 mm
Shank Ø D <sub>s</sub>	20 mm
Feed f in steel < 1100 N/mm <sup>2</sup>	0.69 mm/rev.
Overall length L	153 mm
Tolerance nominal Ø	h7
Standard	DIN 6537
recommended maximum drilling depth L <sub>2</sub>	72.2 mm
Semi-Standard	yes
Series	GARANT Master Steel
Coating	TiAIN
Tool material	solid carbide
Drill depth up to	6×D
Point angle	145 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Colour ring	green
Type of product	Jobber drill

### **Services**

Shank grinding Type HE	129100 HE
------------------------	-----------