

GARANT Master Steel FEED solid carbide drill, plain shank DIN 6535 HA, TiAlN, Ø DC h7: 20 mm or inch



Order data

Order number	122725 20
GTIN	4045197790019
Item class	11E

Description

Version:

- **3-flute drill**, specially developed for use at **very high feed rates**. Outstandingly suitable for **machines with high installed power** and stable operating conditions.
- Special cutter geometry with stable cutting edges and large clearance at the centre enables very high feed rates.
- The patented tip is optimised for chip flow and generates low cutting pressure with good chip breakage.
- · With 145° tip angle for low burr formation when drilling through holes.

The sector-leading technology of the chisel edge guarantees optimum self-centring behaviour and permits spot drilling on irregular surfaces. 3 guide chamfers guarantee a stable exit from the hole and an exact roundness of the hole.

Recommendation:

Maximum drilling depth:

flute length (see table) less $1.5 \times nominal \emptyset$.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Form HB and HE supplied at the same price as HA.

Form HB: order with No. 122726.

Form **HE:** order with **No. 122725 + 129100HE**.

Machining strategy: HPC

Standard: DIN 6537

Tolerance nominal Ø: h7 Number of cutting edges Z: 3

Semi-Standard: yes Tolerance nominal Ø: h7

recommended maximum drilling depth L₂: 71 mm

Overall length L: 153 mm

Shank Ø D_s: 20 mm

Feed f in steel < 1100 N/mm²: 0.69 mm/rev.

Technical description

Feed f in steel < 1100 N/mm ²	0.69 mm/rev.
Nominal Ø D _c	20 mm
Tolerance nominal Ø	h7
Shank Ø D _s	20 mm
Overall length L	153 mm
Standard	DIN 6537
Number of cutting edges Z	3
Flute length L _c	101 mm
recommended maximum drilling depth L ₂	71 mm
Semi-Standard	yes
Series	GARANT Master Steel
Coating	TiAIN
Tool material	solid carbide
Drill depth up to	6×D
Point angle	145 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Tillough-coolant	, ,
Machining strategy	HPC
-	·

Services

Shank grinding Type HE	129100 HE
------------------------	-----------