## Garant

# GARANT Master Steel FEED solid carbide drill, plain shank DIN 6535 HA, TIAIN, Ø DC h7: 4,7 mm or inch

ana III

### Order data

Order number	122725 4,7
GTIN	4045197788962
Item class	11E

#### Description

Version:

**3-flute drill**, specially developed for use at **very high feed rates**. Outstandingly suitable for **machines with high installed power** and stable operating conditions.

- Special cutter geometry with stable cutting edges and large clearance at the centre enables very high feed rates.
- The patented tip is optimised for chip flow and generates low cutting pressure with good chip breakage.
- With 145° tip angle for low burr formation when drilling through holes.
- The sector-leading technology of the chisel edge guarantees optimum self-centring

**behaviour** and permits spot drilling on irregular surfaces. 3 guide chamfers guarantee a stable exit from the hole and an exact roundness of the hole.

#### **Recommendation:**

Maximum drilling depth:

flute length (see table) less  $1.5 \times nominal \emptyset$ .

#### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ . Form HB and HE supplied at the same price as HA. Form **HB**: order with **No. 122726**. Form **HE**: order with **No. 122725 + 129100HE**. Machining strategy: HPC Standard: DIN 6537 Tolerance nominal Ø: h7 Number of cutting edges Z: 3 Semi-Standard: yes Tolerance nominal Ø: h7 recommended maximum drilling depth L<sub>2</sub>: 29 mm Overall length L: 74 mm

## Data sheet

Shank  $\emptyset$  D<sub>s</sub>: 6 mm Feed f in steel < 1100 N/mm<sup>2</sup>: 0.28 mm/rev.

## **Technical description**

Tolerance nominal $\varnothing$	h7
Feed f in steel < 1100 N/mm <sup>2</sup>	0.28 mm/rev.
Overall length L	74 mm
Number of cutting edges Z	3
Flute length L <sub>c</sub>	36 mm
Nominal Ø D <sub>c</sub>	4.7 mm
Standard	DIN 6537
Shank Ø D <sub>s</sub>	6 mm
recommended maximum drilling depth L <sub>2</sub>	29 mm
Semi-Standard	yes
Series	GARANT Master Steel
Coating	TiAIN
Tool material	solid carbide
Drill depth up to	6×D
Point angle	145 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Colour ring	green
Type of product	Jobber drill

## Services

Shank grinding Type HE

129100 HE