Garant

GARANT Master Steel FEED solid carbide drill, plain shank DIN 6535 HA, TIAIN, Ø DC h7: 5,9 mm or inch

ana III

Order data

| Order number | 122725 5,9 |
|--------------|---------------|
| GTIN | 4045197789082 |
| Item class | 11E |

Description

Version:

3-flute drill, specially developed for use at **very high feed rates**. Outstandingly suitable for **machines with high installed power** and stable operating conditions.

- Special cutter geometry with stable cutting edges and large clearance at the centre enables very high feed rates.
- The patented tip is optimised for chip flow and generates low cutting pressure with good chip breakage.
- With 145° tip angle for low burr formation when drilling through holes.
- The sector-leading technology of the chisel edge guarantees optimum self-centring

behaviour and permits spot drilling on irregular surfaces. 3 guide chamfers guarantee a stable exit from the hole and an exact roundness of the hole.

Recommendation:

Maximum drilling depth:

flute length (see table) less $1.5 \times nominal \emptyset$.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$. Form HB and HE supplied at the same price as HA. Form **HB**: order with **No. 122726**. Form **HE**: order with **No. 122725 + 129100HE**. Machining strategy: HPC Standard: DIN 6537 Tolerance nominal \emptyset : h7 Number of cutting edges Z: 3 Semi-Standard: yes Tolerance nominal \emptyset : h7 recommended maximum drilling depth L_2 : 35.2 mm Overall length L: 82 mm

Data sheet

Shank \emptyset D_s: 6 mm Feed f in steel < 1100 N/mm²: 0.32 mm/rev.

Technical description

| Overall length L | 82 mm |
|--|---------------------|
| Shank Ø D _s | 6 mm |
| Standard | DIN 6537 |
| Number of cutting edges Z | 3 |
| Flute length L _c | 44 mm |
| Feed f in steel < 1100 N/mm ² | 0.32 mm/rev. |
| Nominal Ø D _c | 5.9 mm |
| Tolerance nominal Ø | h7 |
| recommended maximum drilling depth L_2 | 35.2 mm |
| Semi-Standard | yes |
| Series | GARANT Master Steel |
| Coating | TiAIN |
| Tool material | solid carbide |
| Drill depth up to | 6×D |
| Point angle | 145 degrees |
| Shank | DIN 6535 HA to h6 |
| Through-coolant | yes, with 25 bar |
| Machining strategy | HPC |
| Colour ring | green |
| Type of product | Jobber drill |
| | |

Services

Shank grinding Type HE

129100 HE