

GARANT Master Steel FEED solid carbide drill, plain shank DIN 6535 HA, TiAlN, Ø DC h7: 5/16 mm or inch



Order data

Order number	122725 5/16
GTIN	4045197957153
Item class	11E

Description

Version:

- **3-flute drill**, specially developed for use at **very high feed rates**. Outstandingly suitable for **machines with high installed power** and stable operating conditions.
- Special cutter geometry with stable cutting edges and large clearance at the centre enables very high feed rates.
- The patented tip is optimised for chip flow and generates low cutting pressure with good chip breakage.
- · With 145° tip angle for low burr formation when drilling through holes.

The sector-leading technology of the chisel edge guarantees optimum self-centring behaviour and permits spot drilling on irregular surfaces. 3 guide chamfers guarantee a stable exit from the hole and an exact roundness of the hole.

Recommendation:

Maximum drilling depth:

flute length (see table) less $1.5 \times \text{nominal } \emptyset$.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Form HB and HE supplied at the same price as HA.

Form HB: order with No. 122726.

Form **HE:** order with **No. 122725 + 129100HE**.

Machining strategy: HPC

Standard: DIN 6537

Tolerance nominal Ø: h7

Number of cutting edges Z: 3

Semi-Standard: yes

Tolerance nominal Ø: h7

recommended maximum drilling depth L₂: 41.1 mm

Overall length L: 91 mm

Shank Ø D_s: 8 mm

Feed f in steel < 1100 N/mm²: 0.37 mm/rev.

Technical description

Feed f in steel < 1100 N/mm ²	0.37 mm/rev.
Overall length L	91 mm
recommended maximum drilling depth L ₂	41.1 mm
Tolerance nominal Ø	h7
Shank Ø D _s	8 mm
Standard	DIN 6537
Flute length L _c	53 mm
Inch nominal Ø corresponds to	7,94 mm
Number of cutting edges Z	3
Semi-Standard	yes
Series	GARANT Master Steel
Coating	TiAlN
Tool material	solid carbide
Drill depth up to	6×D
Point angle	145 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Colour ring	green
Type of product	Jobber drill

Services

Shank grinding Type HE	129100 HE
------------------------	-----------