Garant

GARANT Master Steel FEED solid carbide drill, plain shank DIN 6535 HA, TIAIN, Ø DC h7: 6,5 mm or inch

ana III

Order data

Order number	122725 6,5
GTIN	4045197789143
Item class	11E

Description

Version:

3-flute drill, specially developed for use at **very high feed rates**. Outstandingly suitable for **machines with high installed power** and stable operating conditions.

- Special cutter geometry with stable cutting edges and large clearance at the centre enables very high feed rates.
- The patented tip is optimised for chip flow and generates low cutting pressure with good chip breakage.
- With 145° tip angle for low burr formation when drilling through holes.
- The sector-leading technology of the chisel edge guarantees optimum self-centring

behaviour and permits spot drilling on irregular surfaces. 3 guide chamfers guarantee a stable exit from the hole and an exact roundness of the hole.

Recommendation:

Maximum drilling depth:

flute length (see table) less $1.5 \times nominal \emptyset$.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$. Form HB and HE supplied at the same price as HA. Form **HB**: order with **No. 122726**. Form **HE**: order with **No. 122725 + 129100HE**. Machining strategy: HPC Standard: DIN 6537 Tolerance nominal \emptyset : h7 Number of cutting edges Z: 3 Semi-Standard: yes Tolerance nominal \emptyset : h7 recommended maximum drilling depth L_2 : 43.3 mm Overall length L: 91 mm

Data sheet

Shank \emptyset D_s: 8 mm Feed f in steel < 1100 N/mm²: 0.37 mm/rev.

Technical description

Tolerance nominal Ø	h7
Standard	DIN 6537
Nominal Ø D _c	6.5 mm
Shank Ø D _s	8 mm
Overall length L	91 mm
Number of cutting edges Z	3
Feed f in steel < 1100 N/mm ²	0.37 mm/rev.
Flute length L _c	53 mm
recommended maximum drilling depth L_2	43.3 mm
Semi-Standard	yes
Series	GARANT Master Steel
Coating	TiAIN
Tool material	solid carbide
Drill depth up to	6×D
Point angle	145 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Colour ring	green
Type of product	Jobber drill

Services

Shank grinding Type HE

129100 HE