

Garant

GARANT Master Steel FEED solid carbide drill, plain shank DIN 6535 HA, TiAlN, Ø DC h7: 7,9 mm or inch



Order data

| | |
|--------------|---------------|
| Order number | 122725 7,9 |
| GTIN | 4045197789280 |
| Item class | 11E |

Description

Version:

3-flute drill, specially developed for use at **very high feed rates**. Outstandingly suitable for **machines with high installed power** and stable operating conditions.

- **Special cutter geometry with stable cutting edges and large clearance at the centre enables very high feed rates.**
- **The patented tip is optimised for chip flow and generates low cutting pressure with good chip breakage.**
- **With 145° tip angle for low burr formation when drilling through holes.**

The **sector-leading technology of the chisel edge** guarantees **optimum self-centring behaviour** and permits spot drilling on irregular surfaces. 3 guide chamfers guarantee a stable exit from the hole and an exact roundness of the hole.

Recommendation:

Maximum drilling depth:

flute length (see table) less 1.5×nominal Ø.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 122726**.

Form **HE**: order with **No. 122725 + 129100HE**.

Machining strategy: HPC

Standard: DIN 6537

Tolerance nominal Ø: h7

Number of cutting edges Z: 3

Semi-Standard: yes

Tolerance nominal Ø: h7

recommended maximum drilling depth L_2 : 41.2 mm

Overall length L: 91 mm

Shank $\varnothing D_s$: 8 mm

Feed f in steel < 1100 N/mm²: 0.37 mm/rev.

Technical description

| | |
|--|---------------------|
| Shank $\varnothing D_s$ | 8 mm |
| Standard | DIN 6537 |
| Tolerance nominal \varnothing | h7 |
| Flute length L_c | 53 mm |
| Number of cutting edges Z | 3 |
| Overall length L | 91 mm |
| Nominal $\varnothing D_c$ | 7.9 mm |
| Feed f in steel < 1100 N/mm ² | 0.37 mm/rev. |
| recommended maximum drilling depth L_2 | 41.2 mm |
| Semi-Standard | yes |
| Series | GARANT Master Steel |
| Coating | TiAlN |
| Tool material | solid carbide |
| Drill depth up to | 6×D |
| Point angle | 145 degrees |
| Shank | DIN 6535 HA to h6 |
| Through-coolant | yes, with 25 bar |
| Machining strategy | HPC |
| Colour ring | green |
| Type of product | Jobber drill |

Services

| | |
|------------------------|-----------|
| Shank grinding Type HE | 129100 HE |
|------------------------|-----------|