

# GARANT Master Steel FEED solid carbide drill, Weldon shank DIN 6535 HB, TiAIN, Ø DC h7: 12,5 mm



#### Order data

Order number	122726 12,5
GTIN	4045197795618
Item class	11E

## **Description**

#### **Version:**

- **3-flute drill**, specially developed for use at **very high feed rates**. Outstandingly suitable for **machines with high installed power** and stable operating conditions.
- Special cutter geometry with stable cutting edges and large clearance at the centre enables very high feed rates.
- The patented tip is optimised for chip flow and generates low cutting pressure with good chip breakage.
- · With 145° tip angle for low burr formation when drilling through holes.

The sector-leading technology of the chisel point guarantees optimum self-centring behaviour and permits spot drilling on irregular surfaces. 3 guide chamfers guarantee a stable exit from the hole and an exact roundness of the hole.

#### **Recommendation:**

### **Maximum drilling depth:**

flute length (see table) less  $1.5 \times \text{nominal } \emptyset$ .

#### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

Standard: DIN 6537
Tolerance nominal Ø: h7
Number of cutting edges Z: 3
Tolerance nominal Ø: h7

recommended maximum drilling depth L₂: 58.3 mm

Overall length L: 124 mm Shank Ø D<sub>s</sub>: 14 mm

Feed f in steel < 1100 N/mm<sup>2</sup>: 0.56 mm/rev.

# **Technical description**

Overall length L	124 mm
Number of cutting edges Z	3
Shank Ø D <sub>s</sub>	14 mm
Flute length L <sub>c</sub>	77 mm
Tolerance nominal Ø	h7
Standard	DIN 6537
Feed f in steel < 1100 N/mm <sup>2</sup>	0.56 mm/rev.
Nominal Ø D <sub>c</sub>	12.5 mm
recommended maximum drilling depth L <sub>2</sub>	58.3 mm
Series	GARANT Master Steel
Coating	TiAlN
Tool material	solid carbide
Drill depth up to	6×D
Point angle	145 degrees
Shank	DIN 6535 HB to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	green
Type of product	Jobber drill