Garant

Solid carbide HPC drill plain shank DIN 6535 HA, TiAIN, Ø DC p6: 17,5 mm



Order data

Order number	122736 17,5
GTIN	4045197567406
Item class	11E

Description

Version:

Cutting chisel edge with **high centring accuracy** due to **strong core and special point geometry.** High roundness and alignment accuracy of the deep hole, thanks to **4 guide chamfers.** Outstanding chip evacuation due to **4 internal cooling channels** from Ø 3.8 mm. Up to 3.7 mm Ø with 2 internal cooling channels. With **140° point angle** and special **j6 cutting edge tolerance** for optimum generation of a pilot hole.

Recommendation:

Maximum drilling depth:

flute length (see table) less $1.5 \times nominal \emptyset$.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

For deep-hole drilling deeper than $12 \times D$ a pilot hole is recommended, and for deep-hole drilling from $20 \times D$ to $30 \times D$ it is essential.

The generation of a pilot hole improves process reliability.

Form HB and HE supplied at the same price as HA. Form **HB**: order with **No. 122738**. Form **HE**: order with **No. 122736 + 129100HE**. Standard: DIN 6537 Tolerance nominal Ø: p6 Number of cutting edges Z: 2 Tolerance nominal Ø: p6 recommended maximum drilling depth L₂: 66.8 mm Overall length L: 143 mm Shank Ø D_s: 18 mm Feed f in steel < 1100 N/mm²: 0.37 mm/rev.

Technical description

roup 🔥

Data sheet

Shank tolerance	h6
Flute length L _c	93 mm
Number of cutting edges Z	2
Nominal Ø D _c	17.5 mm
Feed f in steel < 1100 N/mm ²	0.37 mm/rev.
Tolerance nominal Ø	рб
Shank Ø D _s	18 mm
Overall length L	143 mm
Standard	DIN 6537
recommended maximum drilling depth L_2	66.8 mm
Coating	TiAIN
Tool material	Solid carbide
Drill depth up to	6×D
Point angle	140 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	green
Type of product	Jobber drill

Services

Shank grinding Type HE	129100 HE
------------------------	-----------