

Garant
Solid carbide HPC drill Weldon shank DIN 6535 HB, TiAlN, Ø DC h7: 10,5 mm

Order data

Order number	122765 10,5
GTIN	4045197399168
Item class	11E

Description
Version:

Cutting chisel edge with **high centring accuracy** due to **strong core and special point geometry**.

Convex cutting edges with honed edges and special flute profile for **short chips**, even on long chipping materials.

Recommendation:
Maximum drilling depth:

clamping slot length (see table) less $1.5 \times \text{nominal } \varnothing$.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

NEW GENERATION AVAILABLE!

Recommended successor products are No. 122716 and 122726.

Machining strategy: HPC

Standard: DIN 6537

Tolerance nominal \varnothing : h7

Number of cutting edges Z: 2

Semi-Standard: yes

Tolerance nominal \varnothing : h7

recommended maximum drilling depth L_2 : 55.3 mm

Overall length L: 118 mm

Shank $\varnothing D_s$: 12 mm

Feed f in steel $< 1100 \text{ N/mm}^2$: 0.27 mm/rev.

Technical description

Feed f in steel $< 1100 \text{ N/mm}^2$	0.27 mm/rev.
Flute length L_c	71 mm

Nominal $\varnothing D_c$	10.5 mm
Number of cutting edges Z	2
Shank tolerance	h6
Tolerance nominal \varnothing	h7
Shank $\varnothing D_s$	12 mm
Overall length L	118 mm
Standard	DIN 6537
recommended maximum drilling depth L_2	55.3 mm
Semi-Standard	yes
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	6×D
Point angle	140 degrees
Shank	DIN 6535 HB to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Colour ring	green
Type of product	Jobber drill