

HOLEX
HOLEX Pro Steel solid carbide drill, plain shank DIN 6535 HA, TiAlN, Ø DC h7 (mm or inch): 9/16 mm or inch

Order data

Order number	122776 9/16
GTIN	4045197957399
Item class	12F

Description
Version:
HOLEX Pro Steel:

Straight major cutting edges and a **special flute profile** ensure good chip evacuation. The robust cutting edge geometry ensures high-performance drilling with good process reliability. A wide range of applications in steel materials thanks to a combination of tough ultra-fine grain carbide and extremely wear-resistant coating.

Up to Ø 1.9 with 4 facets, from Ø 2 with relieved cone.

Recommendation:
Maximum drilling depth:

flute length (see table) less 1.5×nominal Ø.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Version HB and HE supplied at the same price as HA.

Form **HB**: state **No. 122777**.

Form **HE**: state **No. 122778**.

Machining strategy: HPC

Standard: DIN 6537

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Tolerance nominal Ø: h7

recommended maximum drilling depth L_2 : 61.6 mm

Overall length L: 133 mm

Shank Ø D_s : 16 mm

Feed f in steel < 900 N/mm²: 0.26 mm/rev.

Technical description

Shank $\varnothing D_s$	16 mm
recommended maximum drilling depth L_2	61.6 mm
Flute length L_c	83 mm
Overall length L	133 mm
Feed f in steel $< 900 \text{ N/mm}^2$	0.26 mm/rev.
Inch nominal \varnothing corresponds to	14,29 mm
Tolerance nominal \varnothing	h7
Standard	DIN 6537
Number of cutting edges Z	2
Series	HOLEX Pro Steel
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	6xD
Point angle	140 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Colour ring	green
Type of product	Jobber drill