



HOLEX Pro Steel solid carbide drill, Weldon shank DIN 6535 HB, TiAlN, Ø DC h7 (mm or inch): 4,5 mm or inch



Order data

| | |
|--------------|---------------|
| Order number | 122777 4,5 |
| GTIN | 4045197833044 |
| Item class | 12F |

Description

Version:

HOLEX Pro Steel:

Straight major cutting edges and a **special flute profile** ensure good chip evacuation. The robust cutting edge geometry ensures high-performance drilling with good process reliability. A wide range of applications in steel materials thanks to a combination of tough ultra-fine grain carbide and extremely wear-resistant coating.

Recommendation:

Maximum drilling depth:

clamping slot length (see table) less 1.5×nominal Ø.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$

Machining strategy: HPC

Standard: DIN 6537

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Tolerance nominal Ø: h7

recommended maximum drilling depth L_2 : 29.3 mm

Overall length L: 74 mm

Shank Ø D_s : 6 mm

Feed f in steel < 900 N/mm²: 0.14 mm/rev.

Technical description

| | |
|---|--------------|
| Feed f in steel < 900 N/mm ² | 0.14 mm/rev. |
| Number of cutting edges Z | 2 |

| | |
|--|-------------------|
| Flute length L_c | 36 mm |
| Overall length L | 74 mm |
| Standard | DIN 6537 |
| Nominal $\varnothing D_c$ | 4.5 mm |
| Tolerance nominal \varnothing | h7 |
| Shank $\varnothing D_s$ | 6 mm |
| recommended maximum drilling depth L_2 | 29.3 mm |
| Series | HOLEX Pro Steel |
| Coating | TiAlN |
| Tool material | Solid carbide |
| Drill depth up to | 6xD |
| Point angle | 140 degrees |
| Shank | DIN 6535 HB to h6 |
| Through-coolant | yes, to 25 bar |
| Machining strategy | HPC |
| Colour ring | green |
| Type of product | Jobber drill |