

## Garant

**Solid carbide HPC drill plain shank DIN 6535 HA H7, TiAlN, Ø DC: 8,01 mm**



### Order data

Order number	122790 8,01
GTIN	4045197059178
Item class	11E

### Description

#### Version:

**Drilling and reaming in a single operation.** Cutting chisel edge with **high centring accuracy** due to **strong core and special point geometry**. Particularly high alignment accuracy due to **4 guide chamfers**.

#### Advantage:

Very tight **manufacturing tolerances** with **H7 fit** can be produced without additional reaming.

#### Recommendation:

#### Maximum drilling depth:

Flute length (see table) less 1.5×nominal Ø.

#### Note:

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 122790 + 129100HB** .

Form **HE**: order with **No. 122790 + 129100HE**.

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

Solid carbide precision fit drills for machining aluminium available on request.

Machining strategy: HPC

Bore Ø tolerance: H7

Standard: DIN 6537

Number of cutting edges Z: 2

Bore Ø tolerance: H7

recommended maximum drilling depth  $L_2$ : 41 mm

Overall length L: 91 mm

Shank Ø  $D_s$ : 8 mm

Feed f in steel < 900 N/mm<sup>2</sup>: 0.22 mm/rev.

### Technical description

Flute length $L_c$	53 mm
Nominal $\varnothing D_c$	8.01 mm
Feed $f$ in steel $< 900 \text{ N/mm}^2$	0.22 mm/rev.
Shank tolerance	h6
Number of cutting edges $Z$	2
Shank $\varnothing D_s$	8 mm
Overall length $L$	91 mm
Standard	DIN 6537
recommended maximum drilling depth $L_2$	41 mm
Bore $\varnothing$ tolerance	H7
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	6xD
Point angle	140 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Colour ring	green
Type of product	Jobber drill

## Services

Shank grinding Type HB	129100 HB
Shank grinding Type HE	129100 HE