

## Garant

### Solid carbide drill plain shank DIN 6535 HA 180°, TiAlN, Ø DC m7: 5,4 mm



## Order data

Order number	122793 5,4
GTIN	4045197744821
Item class	11E

## Description

### Version:

Special point geometry for generating **180° flat-bottomed holes**. Low radial forces even when spot drilling on faces with up to 15° slope. Flute geometry for optimum chip evacuation. With 4 guide chamfers to stabilise the drill in the hole.

### Advantage:

**The 180° point angle** permits drilling and counterboring in a single operation.

### Recommendation:

When using the solid carbide 180° drill it is absolutely essential for process reliability:

- **when spot drilling on flat surfaces to drill a pilot hole 1×D using pilot drill No. 122736.**
- **when spot drilling on sloping surfaces up to max. 15° : reduce the feed rate  $f$  to 25% of the stated value. After spot drilling, the normal feed rate value can be used.**

### Note:

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 122793 + 129100HB** .

Form **HE**: order with **No. 122793 + 129100HE**.

180° solid carbide drills for machining aluminium available on request.

**Not** suitable for generating counterbores for socket-head screws to DIN974-1.

Standard: Manufacturer's standard

Tolerance nominal Ø: m7

Number of cutting edges Z: 2

Tolerance nominal Ø: m7

recommended maximum drilling depth  $L_2$ : 35.9 mm

Overall length L: 82 mm

Shank Ø  $D_s$ : 6 mm

Feed  $f$  in steel < 900 N/mm<sup>2</sup>: 0.12 mm/rev.

## Technical description

Shank tolerance	h6
Shank $\varnothing D_s$	6 mm
Overall length L	82 mm
Flute length $L_c$	44 mm
Feed f in steel < 900 N/mm <sup>2</sup>	0.12 mm/rev.
Tolerance nominal $\varnothing$	m7
Standard	Manufacturer's standard
Nominal $\varnothing D_c$	5.4 mm
Number of cutting edges Z	2
recommended maximum drilling depth $L_2$	35.9 mm
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	5×D
Point angle	180 degrees
Shank	DIN 6535 HA to h6
Use for drilling	limited convexity
Use for drilling	limited cross-drilling
Use for drilling	limited oblique spot drilling
Through-coolant	yes, with 25 bar
Pilot drill required	yes, pilot drill
Semi-Standard	yes
Colour ring	green
Type of product	Jobber drill

## Services

Shank grinding Type HB	129100 HB
Shank grinding Type HE	129100 HE

