

**Garant**
**Solid carbide drill-reamer with plain shank DIN 6535 HA, TiAlN, Ø DC: 14 mm**

**Order data**

Order number	122795 14
GTIN	4045197540850
Item class	11P

**Description**
**Version:**

**Drilling and reaming in a single operation.** Very high concentricity. With **4 reaming cutting edges** for optimum dimensional accuracy and surface quality as good as reaming.

**Recommendation:**
**Maximum drilling depth:**

flute length (see table) less 1.5×nominal Ø.

**Note:**

Flute length  $L_c = L_2 + 1.5 \times D_c$ .

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 122795 + 129100HB**.

Form **HE**: order with **No. 122795 + 129100HE**.

Through-coolant: yes, with 25 bar

Bore Ø tolerance: H7

Standard: Manufacturer's standard

Number of cutting edges Z: 2

Bore Ø tolerance: H7

recommended maximum drilling depth  $L_2$ : 56 mm

Overall length L: 124 mm

Shank Ø  $D_s$ : 14 mm

Feed f in steel < 900 N/mm<sup>2</sup>: 0.35 mm/rev.

**Technical description**

Flute length $L_c$	77 mm
Shank tolerance	h6
Feed f in steel < 900 N/mm <sup>2</sup>	0.35 mm/rev.

Nominal $\varnothing D_c$	14 mm
Number of cutting edges Z	2
Shank $\varnothing D_s$	14 mm
Overall length L	124 mm
Standard	Manufacturer's standard
recommended maximum drilling depth $L_2$	56 mm
Bore $\varnothing$ tolerance	H7
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	5×D
Point angle	140 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Colour ring	without
Type of product	Jobber drill

## Services

Shank grinding Type HE	129100 HE
Shank grinding Type HB	129100 HB