

Garant
Solid carbide HPC drill Weldon shank DIN 6535 HB, DLC, Ø DC h7: 6,2 mm

Order data

| | |
|--------------|---------------|
| Order number | 122809 6,2 |
| GTIN | 4045197758880 |
| Item class | 11E |

Description
Version:

DLC coating sp^2 of the latest generation with **low coefficient of friction** results in **outstanding chip clearance**. For **high-performance milling** of **aluminium materials**. **High roundness** and **alignment accuracy of the deep hole**, thanks to **6 guide chamfers**.

Recommendation:
Maximum drilling depth:

clamping slot length (see table) less $1.5 \times \text{nominal } \varnothing$.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Standard: Manufacturer's standard

Tolerance nominal \varnothing : h7

Number of cutting edges Z: 2

Tolerance nominal \varnothing : h7

recommended maximum drilling depth L_2 : 66.7 mm

Overall length L: 114 mm

Shank $\varnothing D_s$: 8 mm

Feed f in aluminium short-chipping: 0.45 mm/rev.

Technical description

| | |
|---------------------------------|--------|
| Overall length L | 114 mm |
| Shank tolerance | h6 |
| Flute length L_c | 76 mm |
| Tolerance nominal \varnothing | h7 |
| Shank $\varnothing D_s$ | 8 mm |

| Standard | Manufacturer's standard |
|--|-------------------------|
| Nominal $\varnothing D_c$ | 6.2 mm |
| Number of cutting edges Z | 2 |
| Feed f in aluminium short-chipping | 0.45 mm/rev. |
| recommended maximum drilling depth L_2 | 66.7 mm |
| Coating | DLC |
| Tool material | solid carbide |
| Drill depth up to | 8xD |
| Type | W |
| Point angle | 135 degrees |
| Cutting direction | right-hand |
| Shank | DIN 6535 HB to h6 |
| Through-coolant | Yes, with 25 bar |
| Machining strategy | HPC |
| Semi-Standard | yes |
| Colour ring | yellow |
| Type of product | Jobber drill |