Garant

Solid carbide HPC drill plain shank DIN 6535 HA, TiAIN, Ø DC m6 (mm or inch): 13 mm or inch



Order data

Order number	123008 13
GTIN	4045197569929
Item class	11E

Description

Version:

Cutting chisel edge with **high centring accuracy** due to **strong core and special point geometry.** High roundness and alignment accuracy of the deep hole, thanks to **4 guide chamfers.** Outstanding chip evacuation due to **4 internal cooling channels** from Ø 3.8 mm. Up to 3.7 mm Ø with 2 internal cooling channels. **Straight major cutting edges** with honed edges and special flute profile for **short chips**, even on long chipping materials.

Recommendation: Maximum drilling depth:

Flute length (see table) less $1.5 \times nominal \emptyset$. **Note:** Form HB and HE supplied at the same price as HA. Form **HB:** order with **No. 123010**. Form **HE:** order with **No. 123008 + 129100HE**. Flute length $L_c = L_2 + 1.5 \times D_c$. Standard: Manufacturer's standard Tolerance nominal \emptyset : m6 Number of cutting edges Z: 2 Tolerance nominal \emptyset : m6 recommended maximum drilling depth L_2 : 111.5 mm Overall length L: 178 mm Shank \emptyset D_s : 14 mm Feed f in stainless steel > 900 N/mm²: 0.2 mm/rev.

Technical description

Flute length L_c

131 mm

Number of cutting edges Z	2
Shank tolerance	h6
Nominal Ø D _c	13 mm
Feed f in stainless steel > 900 N/mm ²	0.2 mm/rev.
Tolerance nominal Ø	тб
Shank Ø D _s	14 mm
Overall length L	178 mm
Standard	Manufacturer's standard
recommended maximum drilling depth L_2	111.5 mm
Coating	TiAIN
Tool material	Solid carbide
Drill depth up to	8×D
Point angle	140 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	blue
Type of product	Jobber drill

Shank grinding T	Jpe HE	129100 HE
------------------	--------	-----------