

Garant

Solid carbide HPC drill plain shank DIN 6535 HA, TiAlN, Ø DC m6 (mm or inch): 3,3 mm or inch



Order data

Order number	123008 3,3
GTIN	4045197569295
Item class	11E

Description

Version:

Cutting chisel edge with **high centring accuracy** due to **strong core and special point geometry**. High roundness and alignment accuracy of the deep hole, thanks to **4 guide chamfers**. Outstanding chip evacuation due to **4 internal cooling channels** from Ø 3.8 mm. Up to 3.7 mm Ø with 2 internal cooling channels. **Straight major cutting edges** with honed edges and special flute profile for **short chips**, even on long chipping materials.

Recommendation:

Maximum drilling depth:

Flute length (see table) less 1.5×nominal Ø.

Note:

Form HB and HE supplied at the same price as HA.

Form **HB**: order with **No. 123010**.

Form **HE**: order with **No. 123008 + 129100HE**.

Flute length $L_c = L_2 + 1.5 \times D_c$.

Standard: Manufacturer's standard

Tolerance nominal Ø: m6

Number of cutting edges Z: 2

Tolerance nominal Ø: m6

recommended maximum drilling depth L_2 : 29.1 mm

Overall length L: 72 mm

Shank Ø D_s : 6 mm

Feed f in stainless steel > 900 N/mm²: 0.06 mm/rev.

Technical description

Number of cutting edges Z	2
---------------------------	---

Feed f in stainless steel > 900 N/mm ²	0.06 mm/rev.
Shank tolerance	h6
Nominal Ø D _c	3.3 mm
Flute length L _c	34 mm
Tolerance nominal Ø	m6
Shank Ø D _s	6 mm
Overall length L	72 mm
Standard	Manufacturer's standard
recommended maximum drilling depth L ₂	29.1 mm
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	8×D
Point angle	140 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	blue
Type of product	Jobber drill

Services

Shank grinding Type HE	129100 HE
------------------------	-----------