Garant

GARANT Master Steel SPEED solid carbide drill, plain shank DIN 6535 HA, TIAIN, Ø DC h7: 14,2 mm

and the former of the

Order data

Order number	123025 14,2
GTIN	4045197844569
Item class	11E

Description

Version:

Developed for use with **very high cutting speeds**. Outstandingly suitable for machines with **low installed power** and high speeds.

- $\cdot\,$ Clear reduction in cutting forces due to special cutter geometry.
- $\cdot\,$ Coating for best wear resistance even at high process temperatures.
- · Polished flutes for good chip clearance.
- A slim chisel point and the special arrangement of the 4 guide chamfers ensure high positioning and alignment accuracy. Optimised micro-geometry for increased working life and performance capability.

Recommendation:

Maximum drilling depth:

flute length (see table) less $1.5 \times nominal \emptyset$.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Versions HB and HE supplied at the same price as HA.

Form **HB:** order with **No. 123026**.

Form **HE:** order with **No. 123025 + 129100HE**.

Standard: Manufacturer's standard

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Tolerance nominal Ø: h7

recommended maximum drilling depth L₂: 130.7 mm

Overall length L: 203 mm

Shank Ø D_s: 16 mm

Feed f in steel < 1100 N/mm²: 0.26 mm/rev.

Technical description

© Hoffmann GmbH Qualitätswerkzeuge

Tolerance nominal \varnothing	h7
recommended maximum drilling depth L_2	130.7 mm
Shank Ø D _s	16 mm
Feed f in steel < 1100 N/mm ²	0.26 mm/rev.
Standard	Manufacturer's standard
Overall length L	203 mm
Flute length L _c	152 mm
Number of cutting edges Z	2
Nominal Ø D _c	14.2 mm
Series	GARANT Master Steel
Coating	TiAIN
Tool material	Solid carbide
Drill depth up to	8×D
Point angle	135 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, with 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	green
Type of product	Jobber drill

Services

Shank grinding Type HE	129100 HE
------------------------	-----------