

Garant

GARANT Master Steel SPEED solid carbide drill, Weldon shank DIN 6535 HB, TiAlN, Ø DC h7: 12,8 mm



Order data

Order number	123026 12,8
GTIN	4045197846945
Item class	11E

Description

Version:

Developed for use with **very high cutting speeds**. Outstandingly suitable for machines with **low installed power** and high speeds.

- **Clear reduction in cutting forces due to special cutter geometry.**
- **Coating for best wear resistance even at high process temperatures.**
- **Polished flutes for good chip clearance.**

A **slim chisel point** and the **special arrangement of the 4 guide chamfers** ensure **high positioning and alignment accuracy**. Optimised micro-geometry for increased working life and performance capability.

Recommendation:

Maximum drilling depth:

clamping slot length (see table) less 1.5×nominal Ø.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Standard: Manufacturer's standard

Tolerance nominal Ø: h7

Number of cutting edges Z: 2

Tolerance nominal Ø: h7

recommended maximum drilling depth L_2 : 113.8 mm

Overall length L: 178 mm

Shank Ø D_s : 14 mm

Feed f in steel < 1100 N/mm²: 0.23 mm/rev.

Technical description

recommended maximum drilling depth L_2	113.8 mm
--	----------

Shank $\varnothing D_s$	14 mm
Tolerance nominal \varnothing	h7
Number of cutting edges Z	2
Overall length L	178 mm
Nominal $\varnothing D_c$	12.8 mm
Feed f in steel < 1100 N/mm ²	0.23 mm/rev.
Flute length L _c	133 mm
Standard	Manufacturer's standard
Series	GARANT Master Steel
Coating	TiAlN
Tool material	Solid carbide
Drill depth up to	8xD
Point angle	135 degrees
Cutting direction	right-hand
Shank	DIN 6535 HB to h6
Through-coolant	yes, to 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	green
Type of product	Jobber drill