Garant

GARANT Master Steel FEED solid carbide drill, plain shank DIN 6535 HA, TIAIN, Ø DC h7 (mm or inch): 10 mm or inch

and the second second

Order data

Order number	123035 10
GTIN	4045197839695
Item class	11E

Description

Version:

3-flute drill, specially developed for **use at very high feed rates**. Outstandingly suitable for **machines with high installed power** and stable operating conditions.

- Special cutter geometry with stable cutting edges and large clearance at the centre enables very high feed rates.
- The patented tip is optimised for chip flow and generates low cutting pressure with good chip breakage.

The sector-leading technology of the drill point guarantees optimum self-centring behaviour. 3 guide chamfers guarantee a stable exit from the hole and an exact roundness of the hole.

Recommendation:

Maximum drilling depth:

flute length (see table) less 1.5×nominal Ø.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Form HB and HE supplied at the same price as HA.

Form HB: order with No. 123036.

Form **HE:** order with **No. 123035 + 129100HE**.

Standard: Manufacturer's standard

Tolerance nominal Ø: h7

Number of cutting edges Z: 3

Tolerance nominal Ø: h7

recommended maximum drilling depth L₂: 80 mm

Overall length L: 142 mm

Shank Ø D₅: 10 mm

Feed f in steel < 1100 N/mm²: 0.44 mm/rev.

Technical description

recommended maximum drilling depth L ₂	80 mm
Feed f in steel < 1100 N/mm ²	0.44 mm/rev.
Overall length L	142 mm
Shank Ø D _s	10 mm
Flute length L _c	95 mm
Number of cutting edges Z	3
Tolerance nominal Ø	h7
Standard	Manufacturer's standard
Nominal Ø D _c	10 mm
Series	GARANT Master Steel
Coating	TiAIN
Tool material	Solid carbide
Drill depth up to	8×D
Point angle	140 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, to 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	green
Type of product	Jobber drill

Services

Shank grinding Type HE	129100 HE
------------------------	-----------