

GARANT Master Steel FEED solid carbide drill, plain shank DIN 6535 HA, TiAlN, Ø DC h7 (mm or inch): 16 mm or inch



Order data

Order number	123035 16
GTIN	4045197840059
Item class	11E

Description

Version:

3-flute drill, specially developed for **use at very high feed rates**. Outstandingly suitable for **machines with high installed power** and stable operating conditions.

- Special cutter geometry with stable cutting edges and large clearance at the centre enables very high feed rates.
- The patented tip is optimised for chip flow and generates low cutting pressure with good chip breakage.

The sector-leading technology of the drill point guarantees optimum self-centring behaviour. 3 guide chamfers guarantee a stable exit from the hole and an exact roundness of the hole.

Recommendation:

Maximum drilling depth:

flute length (see table) less $1.5 \times \text{nominal } \emptyset$.

Note:

Flute length $L_c = L_2 + 1.5 \times D_c$.

Form HB and HE supplied at the same price as HA.

Form HB: order with No. 123036.

Form **HE**: order with **No. 123035 + 129100HE**.

Standard: Manufacturer's standard

Tolerance nominal Ø: h7 Number of cutting edges Z: 3 Tolerance nominal Ø: h7

recommended maximum drilling depth L₂: 128 mm

Overall length L: 203 mm Shank Ø D_s: 16 mm

Feed f in steel < 1100 N/mm²: 0.61 mm/rev.

Technical description

Nominal Ø D _c	16 mm
Flute length L _c	152 mm
Shank Ø D _s	16 mm
Number of cutting edges Z	3
Tolerance nominal Ø	h7
Overall length L	203 mm
recommended maximum drilling depth L ₂	128 mm
recommended maximum drining depth L ₂	
Feed f in steel < 1100 N/mm ²	0.61 mm/rev.
Standard	Manufacturer's standard
Series	GARANT Master Steel
Coating	TiAIN
Tool material	Solid carbide
Drill depth up to	8×D
Point angle	140 degrees
Shank	DIN 6535 HA to h6
Through-coolant	yes, to 25 bar
Machining strategy	HPC
Semi-Standard	yes
Colour ring	green
Type of product	Jobber drill

Services

Shank grinding Type HE 129100 HE	Shank grinding Type HE	129100 HE
----------------------------------	------------------------	-----------